

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) An optical device, comprising:
an encoding surface having a micro-relief pattern over at least part ~~[[.]]~~ thereof, the micro-relief pattern producing ~~designed to produce~~ a predetermined diffracted first image when illuminated in use, and

an optically anisotropic layer, ~~provided~~

~~whereby~~ wherein at least part of said micro-relief pattern induces local orientation of said optically anisotropic layer thereby to impose a predetermined polarization modulation, thereby to produce a predetermined second polarized image when illuminated in use.

2. (original) An optical device according to Claim 1, wherein said micro-relief pattern is provided on a layer in contact with said optically anisotropic layer thereby to define said encoding surface.

3. (original) An optical device according to Claim 1, wherein said encoding surface is formed on the optically anisotropic layer.

4. (previously presented) An optical device according to claim 1, wherein said encoding surface includes one or more regions having a significant diffractive effect and one or more relatively weakly diffractive regions where there is little or no diffractive effect.

5. (previously presented) An optical device as claimed in claim 1, wherein said encoding surface includes a plurality of areas, each of which having a respective orientation of the micro-relief pattern thereon, defining respective optical axes of the optically anisotropic layer.

6. (currently amended) An optical device according to claim 1, wherein ~~[[the]]~~ a coating thickness of at least part of the optically anisotropic layer is selected having regard to the frequency of the intended illumination in use, to provide phase retardation when appropriately viewed.

7. (currently amended) An optical device according to claim ~~[[1]]~~ 2, wherein ~~[[the]]~~ a coating thickness of at least part of the optically anisotropic layer is selected having regard to the frequency, of the intended illumination in use, to provide a phase retardation when appropriately viewed.

8. (previously presented) An optical device according to claim 1, wherein at least one of: the average thickness of the optically anisotropic layer, and its birefringence varies with position across said device to vary the optical retardation induced thereby.

9. (previously presented) An optical device according to claim 1 wherein the encoding surface is stepped, whereby the thickness of the optically anisotropic layer is stepped by a step distance which is substantially greater than the structure pitch dimension, thereby to provide regions of respective selected retardations.

10. (original) An optical device according to Claim 8, wherein the thickness of said optically anisotropic layer, disregarding the micro-relief pattern is generally continuously contoured.

11. (original) An optical device according to Claim 10, wherein the thickness of said optically anisotropic material, disregarding the micro-relief pattern, varies linearly in at least one dimension.

12. (previously presented) An optical device according to claim 1, wherein the encoding surface is reflective over at

least part of the device, whereby at least part of said device is adapted to operate in reflection mode.

13. (previously presented) An optical device according to claim 1, wherein at least part of the surface of the optically anisotropic layer remote from the encoding surface is at least partially reflective.

14. (original) An optical device according to Claim 2, wherein the micro-relief layer comprises a transmissive substrate and at least part of the surface thereof remote from the interface with the optically anisotropic layer is reflective.

15. (previously presented) An optical device according to claim 1, adapted to operate in use in transmission mode.

16. (previously presented) An optical device according to claim 1, adapted to operate in use in reflection mode.

17. (previously presented) An optical device according to claim 1, wherein said optically anisotropic layer comprises a polymerisable liquid crystalline material.

18. (previously presented) An optical device according to claim 1, wherein said optically anisotropic layer comprises a polymer liquid crystal material.

19. (previously presented) An optical device according to claim 1, wherein the orientation of said optically anisotropic layer is permanently preserved by a fixing process.

20. (currently amended) An optical device according to Claim 2, wherein the refractive index of the micro-relief layer is substantially equal to the ordinary or extraordinary refractive index of the optically anisotropic layer.

21. (original) A method of producing an optical device which comprises providing an encoding surface having a micro-relief pattern over at least part thereof designed to provide a predetermined diffracted first image when illuminated in use, and providing an optically anisotropic layer wherein at least part of said micro-relief pattern induces local orientation of said optically anisotropic layer thereby to impose a predetermined polarization modulation thereby to produce a predetermined second image when illuminated in use.

22. (original) A method according to Claim 21, which includes providing a micro-relief layer and applying said layer

of optically anisotropic material thereto thereby to define said encoding surface.

23. (previously presented) A method according to Claim 21, wherein said micro-relief pattern is formed by embossing.

24. (previously presented) A method according to Claim 21, wherein said micro-relief pattern is formed by UV curing of a suitable material in contact with a master.

25. (previously presented) A security device including an optical device according to claim 1.

26. (previously presented) A bank note including an optical device according to claim 1.

27. (previously presented) A security document including an optical device according to claim 1.

28. (previously presented) An Identification Card including an optical device according to claim 1.

29. (previously presented) A container including an optical device according to claim 1.

30. (previously presented) Packaging including an optical device according to claim 1.

31. (previously presented) A data storage device including an optical device according to claim 1.

32. (previously presented) A method of authentication of an article or substance, which comprises applying to said article or substance an optical device in accordance with claim 1, and thereafter examining said article or substance for the presence of at least one of said first and second images.